



**Type 450D/452D Slotted stainless steel grate**



**Product Features**

- Certified to EN 1433 Load Class A - 3,500 lbs - 70 psi
- Uses 'DrainLok' boltless locking system
- Suitable for use with K100, KS100, and H100K-8 channels
- Manufactured from 16 gauge, grade 304 stainless steel
- Bicycle Tire Penetration Resistant to AS3996-2006



ACO Specification Information

**Specifications**

*General*  
 The surface drainage system shall be ACO Drain K100, KS100, and H100K-8 channels\*, complete with ACO Type 450D/452D Slotted stainless steel grate with 'DrainLok' locking as manufactured by ACO, Inc. or similar approved.

*Materials*  
 The covers shall be manufactured from stainless steel and have **minimum** properties as follows:

- **Independently certified to meet Load Class A to EN 1433 - 3,500 lbs - 70 psi**
- **16 gauge, Grade 304 stainless steel**
- **Intake area of 17.6 sq. in. (113.5 cm<sup>2</sup>) per half meter of grate**

The overall width of 4.84" (123mm) and overall length of 39.37" (1000mm) (Type 450D) and 19.69" (500mm) (Type 452D). Slots measure 1.46" (37.08mm) by 0.38" (10mm).

*Installation*  
 The trench drain system and grates shall be installed in accordance with the manufacturer's installation instructions and recommendations.


\* delete as appropriate

# ACO DRAIN

## Type 450D/452D Slotted stainless steel grate



Plan view




Side elevation



Description	Part No.	Length inches (mm)	Width inches (mm)	Weight lbs.
<b>DrainLok grates</b>				
Type 450D Slotted stainless steel grate	<b>12640</b>	39.37 (1000)	4.84 (123)	5.9
Type 452D Slotted stainless steel grate	<b>12641</b>	19.69 (500)	4.84 (123)	3.0

### 'DrainLok' locking mechanism



ACO DrainLok™ is a patented, boltless locking system that removes the need for bolts and bars and improves the hydraulic capacity of the channel. The DrainLok™ mechanism simply clips into the channel edge rail for rapid installation. ACO DrainLok™ grates are fitted with an anti-shunt mechanism that restricts unwanted grate movement when installed, improving durability and longevity of the system.

**ACO, Inc.**  
**Northeast Sales Office**  
 9470 Pinecone Drive  
 Mentor, OH 44060  
 Tel: (440) 639-7230  
 Toll free: (800) 543-4764  
 Fax: (440) 639-7235

**West Sales Office**  
 825 W. Beechcraft St.  
 Casa Grande, AZ 85122  
 Tel: (520) 421-9988  
 Toll Free: (888) 490-9552  
 Fax: (520) 421-9899

**Southeast Sales Office**  
 4211 Pleasant Road  
 Fort Mill, SC 29708  
 Toll free: (800) 543-4764  
 Fax: (803) 802-1063

Follow us on  
  
**Electronic Contact:**  
 info@ACODrain.us  
 www.ACODrain.us



© April 2018, Inc. This information is believed to be accurate but it is not guaranteed to be so. We cannot assume liability for results that buyer obtains with our product since conditions of use are beyond the control of the company. It is the customer's responsibility to evaluate suitability and safety of product for his own use. ACO, Inc. reserves the right to change the product and specifications without notice.