




Product Features

- Certified to EN 1433 Load Class A - 3,500 lbs - 70 psi
- Grates do not lock down
- Suitable for use with K50/KS50
- Manufactured from 16 gauge, grade 304 stainless steel
- Bicycle Tire Penetration Resistant to AS3996-2006



Specifications

General

The surface drainage system shall be ACO Drain MiniKlassik K50 channels complete with ACO MiniKlassik stainless steel slotted grate as manufactured by ACO, Inc. or similar approved.

Materials

The covers shall be manufactured from stainless steel and have **minimum** properties as follows:

- **Independently certified to meet Load Class A to EN 1433 - 3,500 lbs - 70 psi**
- **16 gauge, Grade 304 stainless steel**
- **Intake area of 18.7 sq. in. (120.6 cm²) per meter grate**


The overall width of 2.95" (75mm) and overall length of 39.37" (1000mm). Slots measure 1.35" (34mm) by 0.38" (10mm).

Installation


The trench drain system and grates shall be installed in accordance with the manufacturer's installation instructions and recommendations.

ACO DRAIN

MiniKlassik - Slotted stainless steel grate



Plan view



Side elevation



Description	Part No.	Length inches (mm)	Width inches (mm)	Weight lbs.
MiniKlassik stainless steel slotted grate	95545	39.37 (1000)	2.95 (75)	4.0

ACO, Inc.
Northeast Sales Office
 9470 Pinecone Drive
 Mentor, OH 44060
 Tel: (440) 639-7230
 Toll free: (800) 543-4764
 Fax: (440) 639-7235

West Sales Office
 825 W. Beechcraft St.
 Casa Grande, AZ 85122
 Tel: (520) 421-9988
 Toll Free: (888) 490-9552
 Fax: (520) 421-9899

Southeast Sales Office
 4211 Pleasant Road
 Fort Mill, SC 29708
 Toll free: (800) 543-4764
 Fax: (803) 802-1063



Electronic Contact:
 info@ACODrain.us
 www.ACODrain.us



© April 2018, ACO, Inc. This information is believed to be accurate but it is not guaranteed to be so. We cannot assume liability for results that buyer obtains with our product since conditions of use are beyond the control of the company. It is the customer's responsibility to evaluate suitability and safety of product for his own use. ACO, Inc. reserves the right to change the product and specifications without notice. Reorder# DL164